

BATTERY
SP30720 LITHIUM-ION

ESS RACK SERIES

SCALABLE CAPACITY

30.72kWh



TECHNICAL SPECIFICATIONS

Battery type	LiFePO4
Energy capacity	30.72kWh
Usable capacity	29.4kWh
Nominal capacity	600Ah
Nominal voltage	51.2V
Operating voltage range	44.8V – 57.6V
Cycle life	≥ 6000
Standard charging current	≤ 50A (0.5C)
Max. charging current	≤ 100A (2C)
Standard discharging current	≤ 100A (2C)
Max. discharging current	≤ 150A (3C)
Charging temperature range	0°C~55°C
Discharge temperature range	-20°C~55°C
Storage temperature	-20°C~45°C (<1 month), 0°C~35°C (>1 month)
Relative humidity	15%~90%
Parallel connection	1-6 units
Protection function	Overvoltage/ Undervoltage/ Overcurrent/ Short-circuit/ Reverse connection
Communication interface	RS485/RS232/CAN/GPRS
Pack weight	300±0.5kg
Pack dimensions	663 x 636.3 x 1446.2 mm
IP Protection	IP25
Warranty	5 years
Certification	UN38.3



+256-753390965

info@soleilpower.ug

soleilpowerug